RAW-500S SINGLE HEAD ROTARY ARM STRETCH WRAPPER



NOVA Automation offers a wrapping system for most every pallet load application. Our engineers have addressed all three primary requirements of load wrapping; speed, load stability and protection from the environment. Regardless of your wrapping need, NOVA Automation has the answer to your most demanding applications.

Using innovative designs and optimization features not found in any other wrapping system, NOVA can reduce your stretch film usage up to 30%.

Key Features and Options

- Ideally suited for wrapping rates of up to 65 loads per hour
- Programmable Film Pre-stretch up to 300% is precisely controlled by digital input via the HMI
- 6" color HMI offers advanced diagnostic, operations, and maintenance functions
- Wire mesh conveyor bed is supported by 2.5" rollers on 3.5" centers
- Innovative Cut-N-Tuck design to secure the film tail into the pallet wrap
- Film break prevention using adjustable load cell film tension via HMI
- Optional in-cycle top film applicator for environmental protection
- Synchronized speed controls to ensure film delivery, carriage travel, and turntable operate in unison
- Name brand components offer ease of maintenance
- Easily interfaced with all types of pallet loading systems







Typical System Configuration



TECHNICAL SPECIFICATIONS

Product Speed: Up to 65 loads per hour

Maximum Load Size: 55" L x 55" W x 100" H (can accommodate custom sizes)

Film Stretch: Up to 300%

Film Size: 10" Diameter and 20" to 30" roll height

Pallet Conveyors: Wire mesh over 2.5" precision rollers

In-Cycle Top Film: Optional

Control System: PLC with 6" color HMI with advanced diagnostics (10" HMI available)

Dimensions: 171" L x 96" W x 136" H

Approx. Shipping Weight: 4930 lbs.

Utility Requirements: 480V, 3Ø, 60A - 5 CFM compressed air (international power options available)

The illustrations do not necessarily show the exact design of the products at any given time. The products have to be used in conformity with common practice and all applicable safety regulations. Specifications for products and equipment presented here can be changed without prior notice.